



## CA-CFTR-PS-NC Product Description


This PUR (polyurethane) shielded cable has a T7 right angle connector at one end and unterminated wires at the other end. The cable has a built-in 120-ohm terminating resistor across pin 4 and pin 5. This cable is used with RS485 versions of US Digital's T7 Networked Absolute Inclinometer (<https://www.usdigital.com/products/inclinometers/t7/>).



**WARNING:** This product can cause exposure to substances, such as *phthalate plasticizers*, known to the State of California to cause cancer and reproductive harm. For more information, go to [oehha.ca.gov/proposition-65](https://oehha.ca.gov/proposition-65) (<https://oehha.ca.gov/proposition-65>).

## Specifications

### PIN-OUT




PIN	COLOR	DESCRIPTION
1	Drain	Shield
2	Red	+VCAN
3	Black	GND
4	White	TXD / BUS+
5	Blue	RXD / BUS-



## Notes

- US Digital® warrants its products against defects in materials and workmanship for two years. See complete warranty (<https://www.usdigital.com/company/warranty>) for details.

## Configuration Options



**PLEASE NOTE: This chart is for informational use only.** Certain product configuration combinations are not available. Visit the CA-CFTR-PS-NC product page (<https://www.usdigital.com/products/CA-CFTR-PS-NC>) for pricing and additional information.